UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.	
10/534,211	01/23/2006	Shaohua Yu 18	8017-004US1/C05W0012/02	U 5190	
26161 FISH & RICHA	7590 03/18/200 ARDSON PC	9	EXAMINER		
P.O. BOX 1022			HO, CH	UONG T	
MINNEAPOLI	S, MN 55440-1022		ART UNIT	PAPER NUMBER	
			2419		
			NOTIFICATION DATE	DELIVERY MODE	
			03/18/2009	ELECTRONIC	

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

PATDOCTC@fr.com

Office Action Summary		Α	pplication No.	Applicant(s)				
		1	0/534,211	YU, SHAOHUA	YU, SHAOHUA			
		E	xaminer	Art Unit				
		С	HUONG T. HO	2419				
Period fo	The MAILING DATE of this communi or Reply	cation appear	s on the cover sheet	with the correspondence	address			
WHIC - Exter after - If NC - Failu Any r	CRTENED STATUTORY PERIOD FOR CHEVER IS LONGER, FROM THE MASSISSION OF THE MASSISSION	AILING DATE of 37 CFR 1.136(a unication. tutory period will a will, by statute, cau	E OF THIS COMMUI On the no event, however, may poly and will expire SIX (6) M se the application to become	NICATION. a reply be timely filed ONTHS from the mailing date of thi ABANDONED (35 U.S.C. § 133).				
Status								
1)	Responsive to communication(s) file	d on <i>09 Augu</i>	st 2008					
′=			tion is non-final.					
3)	, 							
٠,١	closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.							
Dispositi	on of Claims		-					
4)⊠	Claim(s) 1.3-11 and 13-22 is/are per	nding in the a	oplication.					
•	Claim(s) <u>1,3-11 and 13-22</u> is/are pending in the application. 4a) Of the above claim(s) is/are withdrawn from consideration.							
	5) Claim(s) is/are allowed.							
′=	Claim(s) <u>1,3-7,9-11,13-17 and 19-22</u>	rejecte	ed.					
·	Claim(s) <u>8 and 18</u> is/are objected to.	10/410 10/000						
•	Claim(s) are subject to restric	tion and/or el	ection requirement.					
		aon ana, or or	oonon roquii omionii.					
	on Papers							
-	The specification is objected to by the		_					
10)	The drawing(s) filed on is/are:		· · · · · · ·	-				
	Applicant may not request that any object			, ,				
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).								
11)☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.								
Priority ι	ınder 35 U.S.C. § 119							
 12) Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f). a) All b) Some coll None of: 1. Certified copies of the priority documents have been received. 2. Certified copies of the priority documents have been received in Application No. 3. Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)). * See the attached detailed Office action for a list of the certified copies not received. 								
2) Notic 3) Inforr	t(s) e of References Cited (PTO-892) e of Draftsperson's Patent Drawing Review (P' nation Disclosure Statement(s) (PTO/SB/08) r No(s)/Mail Date <u>01/23/06</u> .	TO-948)	Paper N	w Summary (PTO-413) lo(s)/Mail Date of Informal Patent Application 				

Art Unit: 2619

DETAILED ACTION

1. The preliminary amendment filed 08/09/08 have been entered and made of record.

2. Claim 1, 3-10, 11, 13-22 are pending.

Information Disclosure Statement

3. The information disclosure statement (IDS) submitted on 01/23/06 was filed. The submission is in compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure statement is being considered by the examiner.

Claim Objections

- 4. Claim 3 is objected to because of the following informalities: Claim 3, line 1 has been written as -- The data transmission apparatus according to **claim 1**, further comprising a ring management unit --; . Appropriate correction is required.
- 5. Claims 8, 18 are objected to because of the following informalities: the acronym "CWDM / DWDM" should be spell out. Appropriate correction is required.
- 6. Claim 13 is objected to because of the following informalities: Claim 13, line 1 has been written as -- The data transmission method according to **claim 11**, further comprising the step of controlling the use of the ringlets in one aggregate pipe --.

 Appropriate correction is required.

Art Unit: 2619

Double Patenting

7. Claims 1, 3-7, 10, 11, 13-17, 19-22 are rejected on the ground of nonstatutory obviousness-type double patenting as being unpatentable over claims 1, 21, 22 of U.S. Patent No. 7,382,789 in view of claim 1 of US Patent No. 7,486,614.

Regarding to claim 1, Yu '789 discloses a data transmission apparatus used in a multiple service ring (claim 21, multiple service ring) including at least two nodes coupled to at least one aggregate pipe and at least one tributary, said apparatus comprising:

a tributary RX framer (claim 21, first tributary RX framing) coupled to a tributary for deframing (claim 21, col. 41, lines 15-20, deframing) data frames received from said tributary and extracting (claim 21, col. 41, lines 15-20, extracting) a destination node address;

a TX framer (claim 21, a first TX framing) for encapsulating (claim 21, col. 41, lines 20-27, encapsulating) the destination node address and the data received from the tributary into frames of the multiple service ring and transmitting the same along an aggregate pipe to a downstream neighbor node in the ring;

a RX framer (claim 22, col. 41, lines 30-50, a second RX framing) for receiving and deframing (claim 22, col. 41, lines 30-45, deframing) data frames of the multiple service ring from a upstream neighbor node along an aggregate pipe to obtain (claim 22, col. 41, lines 30-45, extracting) at least a destination node address and actual data; a filter (claim 22, col. 41, lines 30-45, a second RX filtering) for determining (claim 22,

col. 41, lines 30-45, determining)data frames for local node according to the destination node address, and forwarding the other frames to said TX framer so as to forward the other frames to a next node;

a tributary TX framer (claim 22, col. 41, lines 48-52, the tributary TX framing) for encapsulating (claim 22, col. 41, lines 30-45, converting) said data frames for local node into tributary data frames and sending the tributary data frames to a corresponding tributary.

However, Yu '789 is silent to disclosing wherein each aggregate pipe comprises a N-ring structure consisting of N-M unidirectional ringlets and M unidirectional counterrotating ringlets, where N and M are integers and 1 <= M < N.

Yu '614 discloses wherein each aggregate pipe comprises a N-ring (dual ring, N= 2) structure consisting of N-M unidirectional ringlets (the examiner means N = 2, M = 1) and M (M = 1) unidirectional counter-rotating ringlets (a pair of unidirectional count rotating ringlets), where N and M are integers and 1 <= M < N (claim 1, col. 53, lines 23-27, N = 2, (dual ring), pair of unidirectional ringlets comprises one unidirectional ringlet and one unidirectional count rotating ringlet).

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614 recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base on RPR and to provide the following capabilities such as the technology encapsulation and transport of Ethernet Frame relay.

Regarding to claim 3, Yu '789 discloses the limitations of claim 1 above.

However, Yu '789 is silent to disclosing the data transmission apparatus according to claim 2, further comprising a ring management unit for controlling the use of the ringlets in one aggregate pipe, including assigning a specific (n-1)-th ringlet for transporting data packets in said (n-1)-th ringlet in unidirectional direction and a n-th ringlet for transporting control packets in said n-th ringlet in the opposite direction, where 1 < n <= N.

Yu '614 discloses the data transmission apparatus according to claim 2, further comprising a ring management unit for controlling the use of the ringlets in one aggregate pipe, including assigning a specific (n-1)-th ringlet for transporting data packets in said (n-1)-th ringlet in unidirectional direction and a n-th ringlet for transporting control packets in said n-th ringlet in the opposite direction, where $1 < n \le N$ (claim 34, claim 40, ringlets).

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614 recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base on RPR and to provide the following capabilities such as the technology encapsulation and transport of Ethernet Frame relay.

Regarding to claim 4, Yu '789 discloses the limitations of claim 3 above.

However, Yu '789 is silent to disclosing the data transmission apparatus according to claim 3, wherein said n-th ringlet as a control channel of (n-1)-ringlet is also

Art Unit: 2619

set default as a protection channel of (n-1)th ringlet in the case of fibre facility failure or signal degradation of (n-1)th ringlet

Yu '614 discloses the data transmission apparatus according to claim 3, wherein said n-th ringlet as a control channel of (n-1)-ringlet is also set default as a protection channel of (n-1)th ringlet in the case of fibre facility failure or signal degradation of (n-1)th ringlet (claim 34, claim 40, ringlets).

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614 recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base on RPR and to provide the following capabilities such as the technology encapsulation and transport of Ethernet Frame relay.

Regarding to claim 5, Yu '789 discloses the data transmission apparatus according to claim t, further comprising a tributary identifier setting-up means for setting-up an identifier for indicating the originating tributary, and said tributary identifier are encapsulated together with the destination node address and the data received from the tributary into frames of the multiple service ring (claim 21, encapsulation).

Regarding to claim 6, Yu '789 discloses the data transmission apparatus according to claim 5, further comprising a tributary determining means for determining the tributary type and tributary No. from the data frames for local node, so as to send said tributary data frames to the corresponding tributary (Claim 21, determining).

Regarding to claim 7, Yu '789 discloses the limitations of claim 1 above.

However, Yu '789 is silent to disclosing the data transmission apparatus according to

Page 7

claim 6, wherein said data frames of the MSR are FE/GE/10GE MAC frames.

Yu '614 discloses the data transmission apparatus according to claim 6, wherein said

data frames of the MSR are FE/GE/10GE MAC frames (claim 16, claim 29, MAC

frames).

Thus, it would have been obvious to one of ordinary skill in the art at the time of

the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614

recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base

on RPR and to provide the following capabilities such as the technology encapsulation

and transport of Ethernet Frame relay.

Regarding to claim 10, Yu '789 discloses The data transmission apparatus according to

claim 1, wherein each aggregate pipe includes link and broadcast topologies (claim 5,

claim 10, broadcast).

Regarding to claim 11, Yu '789 discloses a data transmission method used in a multiple

service ring (col. 41, lines 15-28, claim 21, multiple service ring) including at least two

nodes coupled to at least one aggregate pipe and at least one tributary, said method

comprising the steps of:

for data frames from a tributary (col. 41, lines 15-28, claim 21, data frames from a

Art Unit: 2619

tributary),

receiving and deframing (col. 41, lines 15-28, claim 21, deframing) data frames from said tributary (claim 21, a first tributary RX framing) and extracting (claim 21, extracting) a destination node address; and

encapsulating (col. 41, lines 15-28, claim 21, encapsulating) the destination node address and the data received (claim 22, receiving) from the tributary into frames of the multiple service ring and transmitting the same along an aggregate pipe to a downstream neighbor node in the ring;

and for data frames from a upstream neighbor node along an aggregate pipe, receiving and deframing (col. 41, lines 30 - 45, claim 22, deframing) data frames of the multiple service ring from the upstream neighbor node along the aggregate pipe to obtain (col. 41, lines 30 – 45, claim 22, extracting) at least a destination node address and actual data;

determining (col. 41, lines 30 – 45, claim 22, determing) data frames for local node according to the destination node address, and forwarding the other frames to a next node; and

encapsulating (col. 41, lines 30 – 45, claim 22, converting) said data frames for local node into tributary data frames and sending the tributary data frames to a corresponding tributary

However, Yu '789 is silent to disclosing wherein each aggregate pipe comprises a N-ring structure consisting of N-M unidirectional ringlets and M unidirectional counter-rotating ringlets, where N and M are integers and 1 <= M < N.

Yu '614 discloses wherein each aggregate pipe comprises a N-ring (dual ring, N = 2) structure consisting of N-M (M = 1, N (2) – M (1) =1) unidirectional ringlets and M (M = 1) unidirectional counter-rotating ringlets (pair of unidirectional count rotating ringlets), where N and M are integers and 1 <= M < N (claim 1, col. 53, lines 23-27, N = 2, (dual ring); pair of unidirectional ringlets comprises one unidirectional ringlet and one unidirectional count rotating ringlet).

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614 recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base on RPR and to provide the following capabilities such as the technology encapsulation and transport of Ethernet Frame relay.

Regarding to claim 13, claim 13 is rejected the same reasons of claim 3 above.

Regarding to claim 14, claim 14 is rejected the same reasons of claim 4 above.

Regarding to claim 15, claim 15 is rejected the same reasons of claim 5 above.

Regarding to claim 16, claim 16 is rejected the same reasons of claim 6 above.

Regarding to claim 17, claim 17 is rejected the same reasons of claim 7 above.

Regarding to claim 19, claim 19 is rejected the same reasons of claim 9 above.

Regarding to claim 20, claim 20 is rejected the same reasons of claim 10 above.

Regarding to claim 21, Yu '789 discloses the limitations of claim 3 above.

However, Yu '789 is silent to disclosing wherein one of the N ringlets is set as a protection channel for the other ringlets.

Yu '614 discloses wherein one of the N ringlets is set as a protection channel for the other ringlets (claim 6, claim 7, protection or standby channel).

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614 recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base on RPR and to provide the following capabilities such as the technology encapsulation and transport of Ethernet Frame relay.

Regarding to claim 22, Yu '789 discloses the limitations of claim 13 above.

However, Yu '789 is silent to disclosing wherein one of the N ringlets is set as a protection channel for the other ringlets.

Yu '614 discloses wherein one of the N ringlets is set as a protection channel for the other ringlets (claim 6, claim 7, protection or standby channel).

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '614 into the system of Yu '789; since Yu '614

Art Unit: 2619

recited the motivation in col. 1, lines 50-52 which develops Multiplex service flow base on RPR and to provide the following capabilities such as the technology encapsulation and transport of Ethernet Frame relay.

8. Claim 8 is rejected on the ground of nonstatutory obviousness-type double patenting as being unpatentable over the combined system (Yu '789 - Yu '614) in view of claim 1 of US Patent No. 7,428,211.

Regarding to claim 9, the combined system (Yu '789 - Yu '614) disclose the limitations of claim 8 above.

However, the combined system (Yu '789 - Yu '614) are silent to disclosing The data transmission apparatus according to claim 8, wherein said N=I, and M=0, which means the aggregate pipe include a single fibre ring, and all the data frames and control frames are transported in said single fibre ring.

Yu '211 discloses wherein said N=I, and M=0, which means the aggregate pipe include a single fibre ring, and all the data frames and control frames are transported in said single fibre ring (claim 36, single fibre ring)

Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to apply the teaching of Yu '211 into the combined system (Yu '789 - Yu '614), since Yu'211 recited the motivation in the col. 1, lines 50-55 which provides data

Art Unit: 2619

transmission apparatus and method used as RPR MAC Client in MSR based on RPR including RPR Lite for meeting the above needs.

Allowable Subject Matter

9. Claims 8, 18 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

Conclusion

10. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure. Yu (Patent No.: US 6,961,348 B2).

Any inquiry concerning this communication or earlier communications from the examiner should be directed to CHUONG T. HO whose telephone number is (571)272-3133. The examiner can normally be reached on 8:00 am to 4:00 pm.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, EDAN ORGAD can be reached on (571) 272-7884. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2619

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

CH 03/07/09

/Edan Orgad/ Supervisory Patent Examiner, Art Unit 2419